



PRODUCT GROUP # 06 GAS VALVES & ACCESSORIES



GAS BALL VALVES FLARE X F.I.P STYLE BK

MIN. MASTER

6811022	3/8" FLARE X 3/8 FIP GAS BALL VAL. 3.16	10	100
6811032	3/8" OD FLARE X 1/2" FIP GBV 3.16	10	100
6812032	1/2" OD FLARE X 1/2" FIP GAS BALL VALVE 3.16	10	100
6813032	5/8" OD FLARE X 1/2 FIP GAS BALL VAL. 3.16	10	100
6813042	1/2" FLARE X 3/4" FIP GAS BALL VAL. 3.16	10	100



GAS BALL VALVES FLARE X FLARE STYLE BK

MIN. MASTER

6811010	3/8" FLARE X 3/8" FLARE GAS VAL. 9.1	10	140
6812020	1/2" FLARE X 1/2" FLARE GAS BALL VAL. 9.1	10	100
6813333	5/8" FLARE X 5/8" FLARE GAS BALL VAL. 9.1	10	100



GAS CONNECTOR BALL VALVE BK

MIN. MASTER

6814044	5/8" OD FLARE (15"-16"-16 THREAD) X 1/2" FIP	10	100
6814046	5/8" OD FLARE (15"-16"-16 THREAD) X 3/4" FIP	10	100



GAS BALL VALVES STANDARD PORT BK

MIN. MASTER

6823838	3/8" FIP GBV STD PORT 3.16 BK	10	200
6823232	1/2" FIP GBV STD PORT 3.16 BK	10	100
6824242	3/4" FIP GBV STD PORT 3.16 BK	10	100
6825252	1" FIP GBV STD PORT 3.16 BK	10	60



FULL PORT YELLOW LEVER GAS BALL VALVE BC

MIN. MASTER

1510050	1/2" FIP FP-GBV CGA 3.16		12
1510075	3/4" FIP FP-GBV RB LEVER CGA 3.16		10



GAS BALL VALVES BC

MIN. MASTER

6981032	3/8" OD FLARE X 1/2" FIP GBV.3.16 BC		10
6982032	1/2" OD FLARE X 1/2" FIP GBV. 3.16 BC		10
6983232	1/2" FIP X 1/2" FIP GBV.CGA.3.16 BC		10
6984242	3/4" FIP X 3/4" FIP GBV.CGA.3.16 BC.		10

APPLICATIONS & FEATURES

- Max working pressure rated 600 WOG.
- Viton O-ring to prevent stem leakage.
- Fast 1/4 turn open or close operation.
- Hard chromium plated solid ball.
- Bottom entry, blow-out proof stem



NATURAL GAS BBQ INSTALLATION KITS & PARTS

MIN. MASTER

7000110	NG GAS OUTLET BOX W/SAFETY VAL.		1
7200114	ECONOMY BBQ H/U KIT,GAS VALVE & QD & STAY		10
7200115	BBQ H/U KIT W/ LEVER GAS VALVE & QD & STAY		10
7800111	3/8" FEMALE NATURAL GAS QUICK DISCONNECT.		60
7800116	1/2" MIP X 3/8" MIP BRASS ADPT FOR QD BK		25



QUICK DISCONNECT

MIN. MASTER

7000111	3/8" QUICK DISCONNECT FEMALE		10
7000112	1/2" QUICK DISCONNECT FEMALE		10